

MKP-3072BHP DMX CONSOLE

Brief introduction

- : Electrostatic adsorption technology high temperature baking paint
- : Customized button cap = multilayer composite paint spraying technology, super antifraying, prevent light leak
- : Professional mechanical buttons
- : Imported encoder, high-precision CNC machining, anodizing, aluminum encoder cap
- : Hydraulic screen angle adjustment support structure
- : Small size light weight design {875 * 680 * (high 130 low 80) mm}
- : Core components PCB full board Immersion Gold Process
- : Industrial parts, strict selection, to ensure maximum stability guarantee
- : Fine assembly process, uninterrupted 24-hours ageing test
- : More than two hours of uninterrupted simulate shake test

Electrical parameters:

- : Wide-voltage, low-power consumption ,energy-saving design: AC165-264V Power:. 550W
- : Built-in UPS uninterruptible power supply , zero delayed automatic switching , undervoltage, overvoltage protection
- : Panasonic UPS,dedicated high density maintenance-free batteries
- : B85M-E Motherboard,Intel i7-4790 3.6GHz CPU
- : GTX960 display card, 4G graphics memory, independent game graphics card.
- : ROM-240GB solid state disk
- : RAM- 16GB DDR3 1600

Control settings:

- : A master dimming wheel
- : 4 Attribute value encoder wheel (integration of key functions)
- : A Master Fader (60mm manual)
- : 2 AB Fader (100mm manual)
- : 21 program playback Fader (60mm manual)
- : 42 program store function buttons
- : Two 19-inch wide screen touch screen
- : Full-size command keypad
- : Flight case attached with keyboard and mouse

Interfaces

- : 2 USB 3.0 connector (A type), 4USB 2.0 connector
- : 1 spare USB input port (B type)
- : 1 audio input interface
- : 1 stereo output interface
- : 1 LTC input interface
- : 6 DMX-512 output interface
- : 1 DMX-512 input connector (composite output function)
- : 2 working lamp Interface
- : 1 gigabit network interface
- : 1 MIDI input interface
- : 2 VGA video signal input interface,
- : 1 HDMI signal output interface
- : 2 VGA video signal input interface (external signal from the control console display)
- : 1 HDMI signal output interface (external expansion of a display)

Packing:

Flight case MEAS : 96*81*26 CM

GW: 51 KG

